

# AW 702

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>10.0/75 - 15.3</b>   |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       |  BIAS                      |
| <b>MACHINERY</b>          | EMPACADORA DE HENO /<br>MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ COSECHADORA / MAQUINARIA<br>AGRÍCOLA / REMOLQUE |
| <b>VERSIÓN</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS FREE ROLLING</b> | 119 A8  |



## DIMENSIONES IS STANDARD

|                 |      |                |      |
|-----------------|------|----------------|------|
| <b>SW (MM)</b>  | 274  | <b>RIM REC</b> | 9.00 |
| <b>OD (MM)</b>  | 760  | <b>PR</b>      | 8    |
| <b>SLR (MM)</b> | 351  |                |      |
| <b>RC (MM)</b>  | 2213 |                |      |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.10</b> |
|-------------------|-------------|
| 10 FR             | 1905        |
| 25 FR             | 1620        |
| 30 FR             | 1525        |
| 40 FR             | 1360        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.