

# MULTIMAX MP 527

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>360/70 R 18 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | COMPACT LOADER / TELEHANDLER /<br>COMPACT LOADER / TELEHANDLER |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 142 A8/B   |



## DIMENSIONS IS STANDARD

|                 |      |                |                                  |
|-----------------|------|----------------|----------------------------------|
| <b>SW (MM)</b>  | 360  | <b>RIM REC</b> | 11                               |
| <b>OD (MM)</b>  | 969  | <b>RIM ALT</b> | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC |
| <b>SLR (MM)</b> | 439  | <b>ECE</b>     | E11-106R-002996                  |
| <b>RC (MM)</b>  | 2887 | <b>SRI</b>     | 475                              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  | 4.2  | 4.4  |
|------------|------|------|------|------|------|------|------|------|------|
| 50         | 1275 | 1515 | 1725 | 1965 | 2200 | 2360 | 2650 | -    | -    |
| 40         | 1275 | 1515 | 1725 | 1965 | 2200 | 2360 | 2650 | -    | -    |
| 30         | 1365 | 1620 | 1850 | 2105 | 2360 | 2530 | 2840 | -    | -    |
| 25         | 1415 | 1680 | 1915 | 2180 | 2445 | 2625 | 2945 | -    | -    |
| 10 CYC.    | 1555 | 1910 | 2250 | 2585 | 2945 | 3200 | 3620 | 3820 | 3975 |
| STATIC     | 2380 | 2930 | 3445 | 3965 | 4515 | 4910 | 5550 | 5855 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.