


FL 630 ULTRA

| | |
|---------------------|--|
| TYRE SIZE | 600/55 R 26.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 165 D ; 176 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94044955 | RC (IN) | 160.2 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 52.5 | ECE | E11-106R-006813 |
| SLR (IN) | 22.8 | | |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 3640 | 4210 | 4770 | 5800 | 6700 | 7730 | 8750 | 9420 | 10450 | 11350 |
| 30 | 4410 | 5090 | 5780 | 7010 | 8110 | 9350 | 10590 | 11420 | 12650 | 13750 |
| 25 | 5020 | 5800 | 6580 | 7990 | 9240 | 10650 | 12060 | 13000 | 14410 | 15650 |
| 15 | 5740 | 6650 | 7540 | 9160 | 10590 | 12210 | 13820 | 14900 | 16510 | 17940 |
| 5 | 6550 | 7570 | 8590 | 10430 | 12060 | 13900 | 15740 | 16960 | 18800 | 20440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.