

# AW 909

<b>TIRE SIZE</b>	15.0/55 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	▣ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	141 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94010813	<b>RC (IN)</b>	98.0
<b>SW (IN)</b>	15.4	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	33.5	<b>RIM ALT</b>	13
<b>SLR (IN)</b>	14.8	<b>ECE</b>	E4-106R-001547

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.