


AGRIMAX RT 955

| | |
|---------------------|--|
| TYRE SIZE | 270/95 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 143 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 275 | RIM REC | W 9 |
| OD (MM) | 1683 | RIM ALT | W 8 ; W 10 |
| SLR (MM) | 792 | ECE | E4-106R-000785 |
| RC (MM) | 5169 | SRI | 800 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1120 | 1445 | 1745 | 1910 | 2045 | 2235 | 2430 | 2590 | 2725 | - |
| 40 | 1120 | 1445 | 1745 | 1910 | 2045 | 2235 | 2430 | 2590 | 2725 | - |
| 30 | 1200 | 1550 | 1870 | 2045 | 2190 | 2395 | 2600 | 2775 | 2920 | - |
| 10 | 1545 | 2000 | 2410 | 2640 | 2825 | 3090 | 3355 | 3580 | 3765 | 4090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.