


RIDEMAX IT 697 (M+S)



| | |
|---------------------|--|
| TYRE SIZE | 710/70 R 42 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 180 D ; 185 A8 |

DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 716 | RIM REC | DW23 B |
| OD (MM) | 2068 | ECE | 'E11-106R-005178 |
| SLR (MM) | 926 | SRI | 975 |
| RC (MM) | 6264 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 3760 | 4640 | 5440 | 6320 | 7120 | 8000 |
| 50 | 4060 | 5010 | 5875 | 6825 | 7690 | 8640 |
| 40 | 4350 | 5365 | 6290 | 7310 | 8235 | 9250 |
| 30 | 4510 | 5570 | 6530 | 7585 | 8545 | 9600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.