


AGRIMAX RT 765

| | |
|---------------------|--|
| TYRE SIZE | 320/70 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / IMPLEMENTS |
| VERSION | SPECIAL |
| TYRE TYPE | TL |
| LI/SS | 116 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94063154 | RC (IN) | 127.8 |
| SW (IN) | 12.6 | RIM REC | W 10 |
| OD (IN) | 43.1 | RIM ALT | W 9; W 11 |
| SLR (IN) | 19.8 | ECE | E11-106R-005827 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 1520 | 1760 | 2020 | 2260 | 2510 | 2760 |
| 30 | 1600 | 1860 | 2120 | 2380 | 2650 | 2900 |
| 25 | 1660 | 1940 | 2220 | 2480 | 2760 | 3020 |
| 20 | 1750 | 2040 | 2330 | 2610 | 2900 | 3170 |
| 5 LT | 2040 | 2370 | 2700 | 3030 | 3360 | 3690 |
| 5 HT | 1750 | 2040 | 2330 | 2610 | 2900 | 3170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.