


# TR 319

<b>TIRE SIZE</b>	<b>26X12.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LANDWIRTSCHAFTLICHE GERÄTE / ERNTEMASCHINE FÜR OBST / GRABENFRÄSE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	116 A3



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94043637	<b>RC (IN)</b>	75.1
<b>SW (IN)</b>	12.5	<b>RIM REC</b>	10.50 AT
<b>OD (IN)</b>	25.2	<b>RIM ALT</b>	8.0 AT; 8.5 AT; 9.0 AT
<b>SLR (IN)</b>	11.4	<b>ECE</b>	E11-106R-003560

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>44</b>
10	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.