


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 900/60 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	189 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94065257	<b>RC (IN)</b>	251.6
<b>SW (IN)</b>	35.4	<b>RIM REC</b>	DW 30B
<b>OD (IN)</b>	84.3	<b>ECE</b>	E11-106R-006165
<b>SLR (IN)</b>	36.9		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	10120	11770	13620	15280	16930	15890	20660
<b>FROM 40 TO 25</b>	11120	12940	14980	16800	18620	20440	22710
20	11340	13190	15280	17130	18980	20840	23160
12	11560	13450	15570	17460	19360	21250	23610
5	12220	14230	16470	18470	20470	22470	24980
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	15560	18110	20960	23510	26060	28600	31790
5 HT	11340	13190	15280	17130	18980	20840	23160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.