


# AGRIMAX RT 657

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>540/65 R 38</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE                              |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 153 D ; 156 A8   |



## DIMENSIUNI US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94062652 | <b>RC (IN)</b> | 199.2          |
| <b>SW (IN)</b>  | 20.9     | <b>RIM REC</b> | W 16 L         |
| <b>OD (IN)</b>  | 65.6     | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (IN)</b> | 29.9     | <b>ECE</b>     | E4-106R-000589 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35    |
|-----------|------|------|------|------|------|------|------|-------|
| 40        | 3870 | 4510 | 5070 | 5630 | 6210 | 6680 | 7410 | 8050  |
| 30        | 4070 | 4740 | 5330 | 5920 | 6510 | 7020 | 7780 | 8450  |
| 25        | 4230 | 4940 | 5560 | 6170 | 6790 | 7320 | 8110 | 8820  |
| 20        | 4450 | 5190 | 5840 | 6480 | 7130 | 7690 | 8520 | 9260  |
| 5 LT      | 5180 | 6050 | 6800 | 7560 | 8310 | 8960 | 9930 | 10790 |
| 5 HT      | 4450 | 5190 | 5840 | 6480 | 7130 | 7690 | 8520 | 9260  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.