

EARTHMAX SR 31



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 31



EARTHMAX SR 31 is an All Steel radial tire specially designed for articulated dump trucks and wheel loaders. It provides extraordinary strength and stability, whilst the non-directional rigid block pattern stands for both excellent traction and maneuverability even on muddy ground. EARTHMAX SR 31 also features a special tread compound which is particularly cut-and-heat resistant. The radial casing structure also provides reduced rolling resistance offering significant fuel savings.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 R 25	TL	L3	**	216 A2	25.00/3.5	-	0	765	1861	818	5555	42	CR
	23.5 R 25	TL	E3/L3	**/*	185 B 195 A2	19.50/2.5	-	200	612	1607	711	4797	34	CR
	26.5 R 25	TL	E3/L3	**/*	193 B 202 A2	22.00/3.0	-	230	689	1742	766	5200	38	CR
	26.5 R 25	TL	L3	**	209 A2	22.00/3.0	-	0	689	1742	766	5200	38	CR
	29.5 R 25	TL	E3/L3	**/*	200 B 208 A2	25.00/3.5	-	270	765	1861	818	5555	42	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
B	216 kg		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
20.5 R 25	TL	E3/L3	**/*	177 B 186 A2	17.00/2.0	--	170					32	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
 E3/L3	 B	 216 kg	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index