


AGRIMAX RT 855

TIRE SIZE	520/85 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	157 A8/B



DIMENSIUNI IS STANDARD

SW (MM)	516	RIM REC	DW 16 L; W 16 A; DD 16
OD (MM)	1951	RIM ALT	DW 18 A; DD 18; W 18 A; DD 18 L
SLR (MM)	858	ECE	E4-106R-000792
RC (MM)	5782	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	2270	2640	3015	3385	3755	4125
40	2270	2640	3015	3385	3755	4125
30	2430	2830	3225	3625	4020	4415
10 LT	3045	3540	4040	4535	5035	5530
10 HT	2430	2830	3225	3625	4020	4415

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.