

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>200/70 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	94 A8/B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	197	<b>RIM REC</b>	W 6
<b>OD (MM)</b>	686	<b>RIM ALT</b>	W 7
<b>SLR (MM)</b>	315	<b>ECE</b>	E4-106R-000607
<b>RC (MM)</b>	2060	<b>SRI</b>	330

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	315	365	420	470	525	580	625	670
40	315	365	420	470	525	580	625	670
30	340	390	450	505	565	620	670	720
10 LT	425	490	560	630	705	775	840	900
10 HT	340	390	450	505	565	620	670	720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.