


AGRIMAX RT 600

| | |
|---------------------|--|
| TYRE SIZE | 620/75 R 26 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / SPREADER / TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 167 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 625 | RIM REC | DW 20 B |
| OD (MM) | 1590 | ECE | E11-106R-002993 |
| SLR (MM) | 730 | SRI | 750 |
| RC (MM) | 4851 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.8 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 2510 | 2890 | 3545 | 3870 | 4255 | 4635 | 5015 | 5450 | - | - |
| 40 | 2510 | 2890 | 3545 | 3870 | 4255 | 4635 | 5015 | 5450 | - | - |
| 30 | 2685 | 3095 | 3795 | 4145 | 4555 | 4960 | 5370 | 5835 | - | - |
| 10 LT | 3365 | 3875 | 4750 | 5190 | 5700 | 6210 | 6725 | 7305 | - | - |
| 10 HT | 2685 | 3095 | 3795 | 4145 | 4555 | 4960 | 5370 | 5835 | - | - |
| 10 CYC. | - | 4125 | 5285 | 5795 | 6720 | 7370 | 8065 | 8760 | 8895 | 9265 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.