

FLOTATION V LINE

| | |
|---------------------------|--------------------------|
| TIRE SIZE | 500/60 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊗ BIAS |
| MACHINERY | SLÄPVA GN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 151 A8/ 148 B |
| LI/SS FREE ROLLING | 163 A8/159 B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94006212 | RC (IN) | 137.4 |
| SW (IN) | 19.7 | RIM REC | AG 16.00 |
| OD (IN) | 46.1 | RIM ALT | 15.00; 17.00 |
| SLR (IN) | 20.1 | ECE | E4-106R-001562 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 41 | 44 | 46 |
|--------------|-------|-------|-------|
| 5 FR | 13920 | 14490 | 15050 |
| 10 FR | 12530 | 13040 | 13550 |
| 20 FR | 11130 | 11600 | 12040 |
| 25 FR | 9940 | 10350 | 10750 |
| 30 FR | 8950 | 9310 | 9640 |
| 5 DW | 9840 | 10250 | 10650 |
| 10 DW | 8860 | 9230 | 9580 |
| 20 DW | 7880 | 8200 | 8520 |
| 25 DW | 7030 | 7320 | 7610 |
| 30 DW | 6330 | 6590 | 6940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.