


AGRIMAX V- FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 480/80 R 46 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR DE ALTA POTENCIA / TRACTOR |
| VERSIÓN | STEEL BELTED SPL |
| TIRE TYPE | TL |
| LI/SS | 175 D |

DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CÓDIGO USA | 94512188 | RC (IN) | 230.5 |
| SW (IN) | 18.9 | RIM REC | DW 16 L |
| OD (IN) | 76.4 | RIM ALT | DW 15 L |
| SLR (IN) | 35.1 | ECE | E11-106R-0010596 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 |
|----------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5400 | 6370 | 7340 | 8180 | 9140 | 9980 | 10950 | 11770 | 12890 | 13840 |
| FROM 40 TO 25 | 5940 | 7000 | 8070 | 8980 | 10040 | 10960 | 12030 | 12930 | 14150 | 15210 |
| 20 | 6060 | 7140 | 8230 | 9160 | 10250 | 11180 | 12270 | 13190 | 14440 | 15520 |
| 12 | 6180 | 7290 | 8400 | 9350 | 10450 | 11400 | 12510 | 13460 | 14730 | 15830 |
| 5 | 6540 | 7700 | 8870 | 9880 | 11040 | 12050 | 13230 | 14230 | 15560 | 16730 |
| UPTO 20 CYC | 6750 | 7950 | 9160 | 10200 | 11410 | 12440 | 13650 | 14680 | 16070 | 17270 |
| UPTO 10 CYC | 8050 | 9490 | 10930 | 12170 | 13610 | 14850 | 16290 | 17530 | 19180 | 20610 |
| UPTO 5CYC | 8820 | 10390 | 11980 | 13340 | 14910 | 16270 | 17860 | 19210 | 21020 | 22600 |
| 5 HT | 6060 | 7140 | 8230 | 9160 | 10250 | 11180 | 12270 | 13190 | 14440 | 15520 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.