

AGRIMAX TURF RT 333

TIRE SIZE	380/70 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / МАШИНА ДЛЯ СБОРА ФРУКТОВ / МИНИ- ТРАКТОР / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	122 A8 ; 122 B



РАЗМЕРЫ US STANDARD

USA CODE	94068821	RC (IN)	126.5
SW (IN)	15.0	RIM REC	W 12
OD (IN)	42.6	RIM ALT	W 11 ; W 13
SLR (IN)	19.1	ECE	E11-106R-007111

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1820	2120	2420	2720	3010	3310
25	1820	2120	2420	2720	3010	3310
20	1960	2280	2600	2910	3230	3540
5 LT	2450	2850	3250	3640	4040	4440
5 HT	1960	2280	2600	2910	3230	3540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.