


# AGRIMAX V- FLECTO

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 600/60 R 28</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTEUR DE FORTE PUISSANCE /<br>TRACTEUR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 157 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>CODE USA</b> | 94058495 | <b>RC (IN)</b> | 166.5           |
| <b>SW (IN)</b>  | 23.1     | <b>RIM REC</b> | DW 20 B         |
| <b>OD (IN)</b>  | 56.7     | <b>RIM ALT</b> | DW 18 L         |
| <b>SLR (IN)</b> | 24.9     | <b>ECE</b>     | E11-106R-004471 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                            | 9    | 12   | 15   | 17    | 20    | 23    |
|--------------------------------------|------|------|------|-------|-------|-------|
| 45                                   | 4540 | 5290 | 6030 | 6780  | 7520  | 8270  |
| <b>FROM 40 TO 25</b>                 | 4990 | 5820 | 6640 | 7450  | 8270  | 9095  |
| 20                                   | 5090 | 5930 | 6770 | 7590  | 8430  | 9270  |
| 12                                   | 5190 | 6050 | 6900 | 7750  | 8600  | 9460  |
| 5                                    | 5490 | 6390 | 7300 | 8190  | 9090  | 10000 |
| <b>*UPTO 5 CYC WITH FRONT LOADER</b> | 6990 | 8150 | 9280 | 10430 | 11570 | 12730 |
| 5 HT                                 | 5090 | 5930 | 6770 | 7590  | 8430  | 9270  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.