

# EM 936 SUPER

|                  |                   |
|------------------|-------------------|
| <b>TIRE SIZE</b> | <b>10.00 - 20</b> |
| <b>UM</b>        | IS STANDARD       |
| <b>MACHINERY</b> | EXCAVATOR         |
| <b>VERSION</b>   | STANDARD          |
| <b>TIRE TYPE</b> | TT                |
| <b>LI/SS</b>     | 146 B             |



## DIMENSIUNI IS STANDARD

|                 |      |                         |           |
|-----------------|------|-------------------------|-----------|
| <b>OD (MM)</b>  | 1080 | <b>RIM ALT</b>          | 7.0 ; 8.0 |
| <b>SLR (MM)</b> | 500  | <b>PR</b>               | 16        |
| <b>RC (MM)</b>  | 3336 | <b>TRA CODE</b>         | E2        |
| <b>RIM REC</b>  | 7.5  | <b>TREAD DEPTH (MM)</b> | 21,5      |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>7.50</b> |
| 50                | 3000        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.