

# XL GRIP (G3)

|                  |                   |
|------------------|-------------------|
| <b>TIRE SIZE</b> | <b>18.00 - 25</b> |
| <b>UM</b>        | US STANDARD       |
| <b>MACHINERY</b> | ГРЕЙДЕР           |
| <b>VERSION</b>   | STANDARD          |
| <b>TIRE TYPE</b> | TL                |



## РАЗМЕРЫ US STANDARD

|                 |          |                                      |           |
|-----------------|----------|--------------------------------------|-----------|
| <b>USA CODE</b> | 94061839 | <b>RIM REC</b>                       | 13.00/2.5 |
| <b>OW (IN)</b>  | 20.1     | <b>RIM ALT</b>                       | 15.00/2.5 |
| <b>OD (IN)</b>  | 63.6     | <b>PR</b>                            | 32        |
| <b>SLR (IN)</b> | 29.1     | <b>TRA CODE</b>                      | G3        |
| <b>RC (IN)</b>  | 188.2    | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 39.69     |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>83</b> |
|------------------|-----------|
| 25               | 19880     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.