

EARTHMAX SR 47 TP



EARTHMAX SR 47 TP

EARTHMAX SR 47 TP (E-4) is an All-Steel radial tyre specially engineered for rigid haul trucks operating in conditions requiring maximum traction and puncture resistance. The E-4 tread depth ensure long wear even on long hauls, thus reducing downtime and increasing productivity. EARTHMAX SR 47 TP is perfect for any task demanding both traction and stability particularly on muddy or slippery terrain. Available in standard and cut-resistant compounds.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø35"	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	390	670	2185	985	6625	73	STD
	24.00 R 35	TL	E4	**	209 B	17.00/3.5	--	333	670	2185	985	6625	73	CR
	24.00 R 35	TL	E4	***	212 B	17.00/3.5	-	390	670	2185	985	6625	73	STD
	24.00 R 35	TL	E4	***	212 B	17.00/3.5	-	333	670	2185	985	6625	73	CR

STD: STANDARD, CR: CUT RESISTANT COMPOUND, STD: STANDARD COMPOUND

TECHNOLOGIES					PERFORMANCES				
									
									
B	212 kg								

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.D. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026



TECHNOLOGIES		PERFORMANCES					
B	212 kg						

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026