


# MULTIMAX MP 522



<b>TYRE SIZE</b>	<b>440/80 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	COMPACT LOADER / COMPACT LOADER
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	156 A8/B

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94052240	<b>RC (IN)</b>	168.4
<b>SW (IN)</b>	17.4	<b>RIM REC</b>	DW 14 L
<b>OD (IN)</b>	55.7	<b>RIM ALT</b>	DW 13; DW 13 L; DW 15 L
<b>SLR (IN)</b>	25.3	<b>ECE</b>	E11-106R-002968

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	23	29	32	35	38	41	44	46	49	52
30	5070	6010	6480	6940	7410	7880	8360	8820	-	-
25	5070	6010	6480	6940	7410	7880	8360	8820	-	-
20	5470	6460	6960	7450	7950	8440	8940	9440	-	-
15	5670	6700	7210	7730	8240	8750	9270	9790	-	-
5 CYC.	6260	7650	8360	9050	9740	10440	11130	11840	12530	13230
STATIC	9610	11750	12810	13880	14950	16020	17080	18140	19210	20280

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.