

# AW 729

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	137 A8
<b>LI/SS FREE ROLLING</b>	149 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94067466	<b>RC (IN)</b>	113.6
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	37.2	<b>ECE</b>	E11-106R-006616
<b>SLR (IN)</b>	16.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	10010
15 FR	8510
20 FR	8010
25 FR	7150
5 DW	7110
15 DW	6045
20 DW	5690
25 DW	5080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.