


# FL 635

<b>TIRE SIZE</b>	<b>620/40 R 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BALER / HARVESTER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	154 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94048038	<b>RC (IN)</b>	127.9
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	42.0	<b>ECE</b>	E4-106R-002399
<b>SLR (IN)</b>	18.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	2410	2760	3100	3850	4380	5050	5730	6250	6860	7530
40	2650	3020	3390	4220	4790	5540	6280	6870	7530	8270
30	3210	3660	4110	5110	5810	6710	7620	8310	9120	10010
25	3600	4110	4620	5740	6530	7540	8550	9340	10240	11240
15	4190	4770	5360	6670	7580	8750	9930	10850	11890	13060
5	4760	5430	6110	7590	8630	9980	11310	12360	13550	14880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.