

# FLOTATION 648

	<b>650/65 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESI / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
	169 A8/165 B
	181 A8/178 B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94030279	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	26.4	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	65.4	<b>ECE</b>	E11-106R-004563
<b>SLR (IN)</b>	28.0	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	35	36
5 FR	24240	24860	25460
10 FR	21810	22380	22920
20 FR	19400	19880	20370
25 FR	17320	17760	18190
30 FR	15590	15980	16530
5 DW	17050	17480	17900
10 DW	15340	15740	16110
20 DW	13650	13990	14320
25 DW	12180	12490	12790
30 DW	10970	11240	11350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.