

# MINEFORCE

|                     |                       |
|---------------------|-----------------------|
| <b>TIRE SIZE</b>    | <b>24.00 - 35</b>     |
| <b>UM</b>           | IS STANDARD           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                |
| <b>MACHINERY</b>    | AUTOBASCULANTĂ RIGIDĂ |
| <b>VERSION</b>      | CUT RESISTANT         |
| <b>TIRE TYPE</b>    | TL                    |



## DIMENSIUNI IS STANDARD

|                 |           |                 |    |
|-----------------|-----------|-----------------|----|
| <b>OD (MM)</b>  | 2190      | <b>PR</b>       | 48 |
| <b>SLR (MM)</b> | 1003      | <b>TRA CODE</b> | E4 |
| <b>RC (MM)</b>  | 6482      |                 |    |
| <b>RIM REC</b>  | 17.00/3.5 |                 |    |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>6.50</b> | <b>8.50</b> |
|-------------------|-------------|-------------|
| 50                | 18500       | -           |
| 10                | -           | 31500       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.