

# FLOTATION 648

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>600/50 - 22.5</b>   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>MIETITREBBIA / SPARGITORE /<br>MIETITREBBIA / ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | DUAL BEAD  |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 156 A8/152 B   |
| <b>LI/SS FREE ROLLING</b> | 169 A8/165 B   |



## DIMENSIONI US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CODICE USA</b> | 94045266 | <b>RC (IN)</b> | 137.8           |
| <b>SW (IN)</b>    | 24.1     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>    | 46.1     | <b>ECE</b>     | E11-106R-004392 |
| <b>SLR (IN)</b>   | 20.1     | <b>PR</b>      | 20              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 44    | 45    | 46    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 17240 | 17580 | 17900 |
| <b>10 FR</b> | 15510 | 15820 | 16110 |
| <b>20 FR</b> | 13790 | 14060 | 14320 |
| <b>25 FR</b> | 12310 | 12550 | 12790 |
| <b>30 FR</b> | 11080 | 11300 | 11350 |
| <b>5 DW</b>  | 11880 | 12110 | 12350 |
| <b>10 DW</b> | 10690 | 10900 | 11110 |
| <b>20 DW</b> | 9500  | 9690  | 9880  |
| <b>25 DW</b> | 8490  | 8650  | 8820  |
| <b>30 DW</b> | 7640  | 7790  | 7830  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.