

# AW 09

<b>TIRE SIZE</b>	<b>380/55 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	IMPLEMENTOS AGRÍCOLAS / REBOQUE / ENFARDADEIRA DE FENO / CEIFEIRA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	125 A8
<b>LI/SS FREE ROLLING</b>	138 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94038077	<b>RC (IN)</b>	98.1
<b>SW (IN)</b>	15.4	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	33.5	<b>ECE</b>	E4-106R-000379
<b>SLR (IN)</b>	14.8		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200
5 DW	5090
15 DW	4330
20 DW	4080
25 DW	3640

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.