


# FORESTMAX

<b>TIRE SIZE</b>	<b>650/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR / SKOTARE
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8 ; 160 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1811	<b>RIM ALT</b>	DW21B; DW23B
<b>SLR (MM)</b>	832	<b>ECE</b>	E11-106R-008829
<b>RC (MM)</b>	5467	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4
50	3060	3420	3510	3870	4185	4320	4500
40	3400	3800	3900	4300	4650	4800	5000
30	3640	4070	4175	4600	4975	5140	5350
25	3775	4220	4330	4775	5160	5330	5550
20	4185	4675	4795	5290	5715	5905	6150
15	4560	5095	5225	5760	6230	6435	6700
10	5100	5700	5850	6450	6970	7200	7500
<b>10 FORESTRY SERVICE</b>	-	-	-	-	-	-	6150
<b>0 FORESTRY SERVICE</b>	-	-	-	-	-	-	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.