DATA SHEET

PRINTED ON
23-04-2026

TR 678

TIRE SIZE	**600/65 - 34**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS / FORESTRY / EXCAVATOR / TRAILER
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	166 A2 ; 162 A6

DIMENSIONS IS STANDARD

SW (MM)	610	**RIM REC**	DW 20 B
OD (MM)	1644	**PR**	16
SLR (MM)	758	**TRA CODE**	LS2
RC (MM)	4916		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.60
30	4750
10	5300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..