


AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | IF 1250/50 R 32 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 201 B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|------------------------|
| USA CODE | 94068876 | RC (IN) | 241.6 |
| SW (IN) | 49.1 | RIM REC | DH44B/1.3 (multipiece) |
| OD (IN) | 81.2 | ECE | E11-106R-006958 |
| SLR (IN) | 35.3 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 14380 | 16300 | 20460 | 22700 | 25250 | 27170 | 29730 | 31970 | --- | --- |
| 25 | 15690 | 17780 | 22310 | 24750 | 27530 | 29620 | 32140 | 34840 | --- | --- |
| 20 | 16790 | 19020 | 23870 | 26480 | 29460 | 31700 | 34690 | 37290 | --- | --- |
| 5 LT | 21020 | 23820 | 29890 | 33160 | 36890 | 39690 | 43430 | 46690 | --- | --- |
| 5 HT | 16790 | 18020 | 23870 | 26480 | 29460 | 31700 | 34690 | 37290 | --- | --- |
| UPTO 5 CYC WITH FRONT LOADER | --- | 26370 | 33770 | 37020 | 42950 | 47100 | 51540 | 55980 | 56880 | 59230 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.