


MULTIMAX MP 513

| | |
|---------------------|--|
| TIRE SIZE | 425/55 R 17 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | UNIVERSALFORDON / GÖDSLINGSBIL / UNIVERSALFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 142 A8/B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94065110 | RC (IN) | 106.5 |
| SW (IN) | 16.6 | RIM REC | 13 |
| OD (IN) | 35.4 | RIM ALT | 13.00 |
| SLR (IN) | 15.7 | ECE | E11-106R-006433 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 | 51 | 58 |
|-----------|------|------|------|------|------|------|------|------|
| 30 | 2280 | 2810 | 3340 | 3800 | 4330 | 4850 | 5380 | 5840 |
| 25 | 2280 | 2810 | 3340 | 3800 | 4330 | 4850 | 5380 | 5840 |
| 20 | 2450 | 3010 | 3570 | 4080 | 4640 | 5200 | 5580 | 6260 |
| 15 | 2540 | 3120 | 3700 | 4220 | 4810 | 5390 | 5790 | 6490 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.