

# AW 708

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>400/60 - 15.5</b>   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | BIAS   |
| <b>MACHINERY</b>          | PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 149 A8   |



## DIMENSIUNI US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94010356 | <b>RC (IN)</b> | 100.9          |
| <b>SW (IN)</b>  | 15.9     | <b>RIM REC</b> | AG 13.00       |
| <b>OD (IN)</b>  | 34.4     | <b>ECE</b>     | E4-106R-001543 |
| <b>SLR (IN)</b> | 15.0     | <b>PR</b>      | 18             |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>65</b> |
|------------------|-----------|
| 5 FR             | 10030     |
| 15 FR            | 8530      |
| 20 FR            | 8020      |
| 25 FR            | 7160      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.