

# FLOTATION TR 678

|                     |   |
|---------------------|---|
|                     | <b>650/45 - 22.5</b>                              |
| <b>UM</b>           | US STANDARD                                       |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | UYGULAMALI MAKINE / RÖMORK /<br>UYGULAMALI MAKINE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
|                     | 166 B   |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94026517 | <b>RC (IN)</b> | 130.0           |
| <b>SW (IN)</b>  | 25.6     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>  | 45.3     | <b>ECE</b>     | E11-106R-004400 |
| <b>SLR (IN)</b> | 19.8     | <b>PR</b>      | 20              |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>65</b> |
| 30               | 11680     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.