


# RIDEMAX IT 697 (M+S)

<b>TIRE SIZE</b>	<b>650/85 R 38 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 D ; 183 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94066322	<b>RC (IN)</b>	247.2
<b>SW (IN)</b>	27.9	<b>RIM REC</b>	DW 23 B
<b>OD (IN)</b>	81.5	<b>RIM ALT</b>	DW 20 B; DW 21 B
<b>SLR (IN)</b>	38.3	<b>ECE</b>	E11-106R-006761

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
40	7770	9590	11240	13060	14720	16530
30	8390	10360	12150	14110	15890	17860
25	9070	11190	13120	15240	17170	19290
20	9330	11510	13490	15670	17660	19840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.