

# AGRIMAX RT 855

|           |                                                                                 |
|-----------|---------------------------------------------------------------------------------|
| TIRE SIZE | 250/85 R 22                                                                     |
| UM        | IS STANDARD                                                                     |
| MACHINERY | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| VERSIÓN   | SPECIAL                                                                         |
| TIRE TYPE | TL                                                                              |
| LI/SS     | 113 A8/B                                                                        |

## DIMENSIONES IS STANDARD

|          |      |         |                 |
|----------|------|---------|-----------------|
| SW (MM)  | 251  | RIM REC | W 8             |
| OD (MM)  | 985  | RIM ALT | W 7             |
| SLR (MM) | 453  | ECE     | E11-106R-002973 |
| RC (MM)  | 2964 | SRI     | 475             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|-----|-----|-----|------|------|------|------|------|
| 50         | 545 | 625 | 715 | 805  | 900  | 990  | 1070 | 1150 |
| 40         | 545 | 625 | 715 | 805  | 900  | 990  | 1070 | 1150 |
| 30         | 585 | 670 | 770 | 865  | 965  | 1065 | 1150 | 1235 |
| 10 LT      | 730 | 835 | 960 | 1085 | 1210 | 1330 | 1440 | 1545 |
| 10 HT      | 585 | 670 | 770 | 865  | 965  | 1065 | 1150 | 1235 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

