


AGRIMAX RT 765M

TIRE SIZE	710/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	166 D



DIMENSIUNI IS STANDARD

SW (MM)	716	RIM REC	DW 23 B
OD (MM)	1959	RIM ALT	DW 25 B
SLR (MM)	859	ECE	E11-106R-005837
RC (MM)	5751	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	2915	3395	3870	4350	4825	5300
50	3065	3565	4065	4565	5065	5565
40	3195	3720	4240	4765	5285	5805
30	3355	3905	4450	5000	5550	6095
10 LT	3910	4550	5190	5830	6470	7105
10 HT	3355	3905	4450	5000	5550	6095

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.