


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>210/95 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	108 A8/B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94028672	<b>RC (IN)</b>	101.0
<b>SW (IN)</b>	8.4	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	33.7	<b>RIM ALT</b>	W 6
<b>SLR (IN)</b>	15.2	<b>ECE</b>	E4-106R-00634

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
<b>30</b>	1040	1190	1370	1540	1720	1900	2050	2210
<b>25</b>	1040	1190	1370	1540	1720	1900	2050	2210
<b>20</b>	1110	1280	1470	1650	1840	2040	2200	2360
<b>5 LT</b>	1390	1600	1840	2070	2310	2550	2760	2950
<b>5 HT</b>	1110	1280	1470	1650	1840	2040	2200	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.