

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 480/80 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 158 A8/B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------------------|
| SW (MM) | 479 | RIM REC | DW 16 A ; W 16 A ; DD 16 |
| OD (MM) | 1936 | RIM ALT | W 16 L ; DD 16 L ; DW 16 L |
| SLR (MM) | 895 | ECE | E4-106R-001731 |
| RC (MM) | 5871 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 50 | 2000 | 2295 | 2635 | 2975 | 3315 | 3655 | 3955 | 4250 |
| 40 | 2000 | 2295 | 2635 | 2975 | 3315 | 3655 | 3955 | 4250 |
| 30 | 2140 | 2460 | 2825 | 3185 | 3550 | 3915 | 4235 | 4550 |
| 10 LT | 2680 | 3080 | 3535 | 3990 | 4445 | 4900 | 5300 | 5695 |
| 10 HT | 2140 | 2460 | 2825 | 3185 | 3550 | 3915 | 4235 | 4550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.