

# SKID POWER HD (A)

|                     |              |
|---------------------|--------------|
| <b>TIRE SIZE</b>    | 23X8.50 - 12 |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS       |
| <b>MACHINERY</b>    | KOMPAKTLADER |
| <b>VERSION</b>      | STANDARD     |
| <b>TIRE TYPE</b>    | TL           |



## ABMESSUNGEN IS STANDARD

|                 |      |                |                   |
|-----------------|------|----------------|-------------------|
| <b>SW (MM)</b>  | 215  | <b>RIM REC</b> | 7.00 I - 55       |
| <b>OD (MM)</b>  | 585  | <b>RIM ALT</b> | 7.00 I - 70; 7 JA |
| <b>SLR (MM)</b> | 271  | <b>PR</b>      | 8                 |
| <b>RC (MM)</b>  | 1764 |                |                   |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>4.40</b> |
|-------------------|-------------|
| 10                | 940         |
| 15                | 745         |
| 25                | 685         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.