

EARTHMAX SR 22 AS

| | |
|---------------------|------------------------|
| TIRE SIZE | 14.00 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | LOADER / GRADER |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 153 A8 ; 175 A2 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|---------|--------------------|-------------------|
| OD (MM) | 1370 | RIM ALT | 9.00 GR; 10.00 VA |
| SLR (MM) | 625 | TRA CODE | G2/L2 |
| RC (MM) | 4141 | STAR RATING | ★ |
| RIM REC | 8.00 TG | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.00 | 2.25 | 2.50 | 2.75 | 3.00 | 3.25 | 3.50 | 3.75 | 5.25 | 5.50 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 40 | 2240 | 2430 | 2650 | 2800 | 3000 | 3250 | 3350 | 3650 | - | - |
| 10 | - | - | - | - | - | - | - | - | 6700 | 6900 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.