

PL 801

| | |
|---------------------|---|
| TIRE SIZE | 7.50 - 15 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ERNTMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ROTORSCHWADER / GABELSTAPLER / ERNTMASCHINE / GABELSTAPLER |
| VERSION | STANDARD |
| TIRE TYPE | TT |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|--------------|
| USA-CODE | 94007325 | RC (IN) | 0 |
| SW (IN) | 8.7 | RIM REC | 6.0 |
| OD (IN) | 32.0 | RIM ALT | 6.00 S ; 6.5 |
| SLR (IN) | 0 | PR | 14 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 135 | 140 |
|--------------------|------|-------|
| 15 LOAD WHEEL | 7560 | - |
| 15 STEER WHEEL | 6395 | - |
| 5 OTHER VEHICLES | 6395 | - |
| 15 OTHER VEHICLES | 4695 | - |
| STATIC SIDE LOADER | - | 10330 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.