


AGRIMAX V-FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 540/65 R 30 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 158 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94062133 | RC (IN) | 171.3 |
| SW (IN) | 21.6 | RIM REC | DW 20 B |
| OD (IN) | 57.6 | RIM ALT | DW 18 L |
| SLR (IN) | 25.6 | ECE | E11-106R-005711 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|--------------------------------------|------|------|------|------|-------|-------|-------|
| 45 | 4340 | 5020 | 5700 | 6470 | 7070 | 7670 | 8520 |
| FROM 40 TO 25 | 4770 | 5520 | 6270 | 7120 | 7770 | 8430 | 9370 |
| 20 | 4860 | 5630 | 6390 | 7250 | 7930 | 8600 | 9560 |
| 12 | 4960 | 5740 | 6510 | 7400 | 8080 | 8760 | 9740 |
| 5 | 5250 | 6070 | 6890 | 7830 | 8540 | 9270 | 10310 |
| *UPTO 5 CYC WITH FRONT LOADER | 6680 | 7730 | 8770 | 9960 | 10880 | 11810 | 13120 |
| 5 HT | 4860 | 5630 | 6390 | 7250 | 7930 | 8600 | 9560 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.