

FL 252

| | |
|---------------------|--|
| TIRE SIZE | 8.15 - 15 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | РОТОРНЫЕ ГРАБЛИ / СЕНОВОРОШИЛКА / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ВИЛОЧНЫЙ ПОГРУЗЧИК |
| VERSION | STANDARD |
| TIRE TYPE | TT |



РАЗМЕРЫ IS STANDARD

| | | | |
|----------------|------|-----------|----|
| SW (MM) | 220 | PR | 14 |
| OD (MM) | 720 | | |
| RIM REC | 7.00 | | |
| RIM ALT | 7 BD | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 10.00 |
|---------------------------|--------------|
| 25 LOAD WHEEL | 3900 |
| 25 STEER WHEEL | 3000 |
| 10 OTHER VEHICLES | 3900 |
| 25 OTHER VEHICLES | 3000 |
| STATIC SIDE LOADER | 4530 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.