


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>380/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	133 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94021666	<b>RC (IN)</b>	158.1
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	53.4	<b>RIM ALT</b>	W 11; W 13
<b>SLR (IN)</b>	23.9	<b>ECE</b>	E4-106R-000597

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2500	2910	3320	3730	4130	4540
25	2500	2910	3320	3730	4130	4540
20	2680	3120	3550	3990	4430	4860
5 LT	3360	3900	4450	5000	5560	6100
5 HT	2680	3120	3550	3990	4430	4860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.