


AGRIMAX V-FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 710/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 181 D |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 715 | RIM REC | DW 24 B |
| OD (MM) | 1961 | RIM ALT | DW 23 B; DW 25 B |
| SLR (MM) | 843 | ECE | E11-106R-006163 |
| RC (MM) | 5773 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|--------------------------------|------|------|------|------|------|-------|-------|
| 70 | 3750 | 4350 | 4950 | 5625 | 6225 | 6825 | 7505 |
| FROM 65 TO 40 | 4125 | 4785 | 5445 | 6185 | 6845 | 7505 | 8250 |
| 30 | 4205 | 4880 | 5550 | 6305 | 6980 | 7655 | 8415 |
| 20 | 4290 | 4975 | 5660 | 6430 | 7115 | 7805 | 8580 |
| 10 | 4535 | 5260 | 5985 | 6800 | 7525 | 8255 | 9075 |
| *UPTO 10 CYC WITH FRONT LOADER | 5775 | 6695 | 7620 | 8655 | 9580 | 10505 | 11550 |
| 10 HT | 4205 | 4880 | 5550 | 6305 | 6980 | 7655 | 8415 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.