

AGRIMAX RT 945

| | |
|---------------------|--------------------------------|
| TIRE SIZE | 320/90 R 46 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / TRACTOR / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 146 A8/B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94044719 | RC (IN) | 206.0 |
| SW (IN) | 12.6 | RIM REC | W 10 |
| OD (IN) | 68.7 | RIM ALT | W 9 ; W 11 |
| SLR (IN) | 31.9 | ECE | E4-106R-001399 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------|------|------|------|------|------|------|------|------|
| 30 | 3040 | 3900 | 4760 | 5220 | 5620 | 6150 | 6600 | - |
| 25 | 3040 | 3900 | 4760 | 5220 | 5620 | 6150 | 6600 | - |
| 20 | 3260 | 4180 | 5100 | 5600 | 6020 | 6590 | 7080 | - |
| 5 | 3570 | 4660 | 5650 | 6750 | 7740 | 8040 | 8930 | 9920 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.