


# AGRIMAX RT 600

750/70 R 26

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BIÇERDÖVER / YAYICI / TRAKTÖR / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	172 A8/B



## UNDEFINED US STANDARD

USA CODE	94073146	RC (IN)	207.4
SW (IN)	30.7	RIM REC	DW 25 B
OD (IN)	68.9	RIM ALT	DW 24 B
SLR (IN)	30.9	ECE	E11-106R-007934

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
30	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
25	5970	6940	7930	8900	9780	10840	11950	12640	13890	-	-
20	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 LT	8010	9310	10630	11930	13230	14540	16030	16950	18630	-	-
5 HT	6400	7440	8490	9520	10570	11610	12800	13550	14880	-	-
5 CYC	-	11170	12730	14290	15850	17420	19200	20310	22320	22670	23610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.