


AGRIMAX SPARGO

TIRE SIZE	VF 380/85 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	160 D



DIMENSIONS IS STANDARD

SW (MM)	380	RIM REC	W 13 A
OD (MM)	1500	RIM ALT	W 12
SLR (MM)	678	ECE	E11-106R-009071-01
RC (MM)	4514	SRI	725

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2
70	2455	2745	3000	3165	3285	3410	3535	3705	3870	3995	4160
FROM 65 TO 40	2655	2970	3240	3420	3555	3690	3825	4005	4185	4320	4500
30	2705	3030	3305	3490	3625	3765	3905	4085	4270	4410	4590
20	2760	3090	3370	3560	3695	3840	3980	4165	4355	4495	4680
10	2920	3265	3565	3765	3910	4060	4210	4405	4605	4755	4950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.