

# AGRIMAX V- FLECTO

**VF 480/80 R 38**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	166 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94067220	<b>RC (IN)</b>	203.5
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	68.2	<b>RIM ALT</b>	DW 15 L
<b>SLR (IN)</b>	30.5	<b>ECE</b>	E11-106R-007168

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5000	5740	6590	7440	8290	9150	10000	10630
<b>FROM 40 TO 25</b>	5500	6320	7250	8180	9120	10050	10990	11680
20	5610	6440	7400	8340	9300	10250	11210	11920
12	5710	6570	7540	8510	9480	10450	11420	12150
5	6050	6940	7970	9010	10030	11060	12090	12850
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	7690	8840	10150	11450	12760	14080	15380	16360
5 HT	5610	6440	7400	8340	9300	10250	11210	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.